DL 12
16
4

MATERIAL SAFETY DATA SHEET

T*H*E LABORATORIES, INC.
P.O. BOX 08231
CLEVELAND, OHIO 44108

*** PRODUCT IDENTIFICATION ***

PRODUCT IDENTIFICATION: T*H*E STUFF

REVISED: 01/25/90
FORMULA: MIXTURE

READY TO USE: USED AS SUPPLIED
CONCENTRATE : TO BE MINIMALLY DILUTED 1 PART TO 15 PARTS WATER

*** PRODUCT COMPONENTS ***

PRODUCT COMPOSITION (CONCENTRATE ONLY)	APPROX. WGT. %	ACGIH TLV	OSHA PEL	CAS REG UNITS	CAS REG NO.
A. HAZARDOUS					
ACETALDEHYDE	0.013	100	100	PPM	75-07-0*
ETHYLENE OXIDE	.0002	1	1	PPM	75-21-8*
ISOPROPYL ALCOHOL		75	75	PPM	
B. NON-HAZARDOUS					

FORMULATION INFORMATION:
THIS SPACE RESERVED FOR SPECIAL USE.

*** PHYSICAL DATA ***

**PRODUCT INFORMATION					
BOILING POINT	:	212	(F)	100	(C)
VAPOR PRESSURE (20C)	:	NA	MM	HG	
VAPOR DENSITY(AIR=1)	:	NA			
FREEZING POINT	:	32	(F)	0	(C)
MELTING POINT	:	NA	(F)	NA	(C)
PHYSICAL STATE	:	LIQUID			
ODOR	:	SCENTED			
COLOR	:	MILKY-WHITE			
ODOR THRESHOLD	:	UNK (PPM)			
SOLUBILITY IN WATER(20C)	:	SOLUBLE			
SOLUBILITY IN ORGANIC SOLVENT	:	SOLUBLE IN ALCOHOLS			
% VOLATILE BY VOLUME	:	50			
EVAPORATION RATE	:	<1	(BUTYL ACETATE=1)		
SPECIFIC GRAVITY	:	0.98	(WATER=1)		
DENSITY	:	982.6	KG/M3		
ACID/ALKALINITY	:	NA	MEQ/G		

*** FIRE AND EXPLOSION DATA ***

FLASH PT: 420 (F) 216 (C) BY PMCC. IGNITION TEMP: NA (F) NA (C)
FLAMMABLE LIMITS IN AIR (%): LOWER: NA UPPER: NA
SENSITIVITY TO MECHANICAL IMPACT (Y/N): N
SENSITIVITY TO STATIC DISCHARGE: STATIC DISCHARGE NOT EXPECTED
EXTINGUISHING MEDIA: ALL STANDARD FIREFIGHTING MEDIA.
SPECIAL FIREFIGHTING PROCEDURES: NONE KNOWN